

# Material Safety Data Sheet

Page 1 of 3

Infosafe No. 2BKCZ Issue Date: November 2002 ISSUED by BOSTIK

Product Name: **PRO FILL A GAP 475GM**

Not classified as hazardous according to criteria of NOHSC

## COMPANY DETAILS

**Company Name** BOSTIK FINDLEY AUSTRALIA PTY LTD (ABN 003 893 838)  
**Address** 51 - 71 High Street Thomastown  
VIC 3074  
**Tel/Fax** Tel: 03 9279 9333 Fax: 03 9279 9270

## IDENTIFICATION

**Product Code** 223522  
**Product Name** PRO FILL A GAP 475GM  
**Proper Shipping Name** None Allocated  
**UN Number** None Allocated  
**DG Class** None Allocated  
**Packing Group** None Allocated  
**Hazchem Code** None Allocated  
**Poisons Schedule** Not Scheduled  
**Product Use** A general purpose, gunnable sealer for metal, masonry, timber and glass.

## Physical Data

**Appearance** White, gunnable paste with slight odour.  
**Boiling Point** Not Available  
**Vapour Pressure** Not Available  
**Specific Gravity** approx. 1.60 g/cm<sup>3</sup>  
**Flash Point** Not Available  
**Flamm. Limit LEL** Not Available

## Other Properties

**pH Value** 7.2-8.2

## Ingredients

<b>Ingredients</b>	<b>Name</b>	<b>CAS</b>	<b>Proportion</b>
	Mineral fillers		60-100 %
	Acrylic polymer		10-30 %
	Additives		1-10 %
	Water		TO 100%

## HEALTH HAZARD INFORMATION

### Health Effects

**Acute - Eye** May be an eye irritant.  
**Acute - Skin** Contact with skin may result in irritation.  
**Acute - Inhaled** Inhalation of high vapour concentrations may cause headache and nausea.  
**Chronic** Prolonged skin contact may cause irritation and defatting.

### First Aid

**Swallowed** If swallowed seek medical advice.  
**Eye** Wash with copious amount of water for 10 minutes. Seek medical attention.  
**Skin** Wipe off excess and wash affected area with plenty of soap and water. Removed contaminated clothing and launder before re-use. If irritation occurs seek medical attention.

Continued on next page

# Material Safety Data Sheet

Page 2 of 3

Infosafe No. 2BKCZ Issue Date: November 2002 ISSUED by BOSTIK

Product Name: **PRO FILL A GAP 475GM**

Not classified as hazardous according to criteria of NOHSC

**Inhaled** Not a likely hazard under normal use. However, should inhalation occur, remove patient to fresh air and seek medical advice.

**First Aid Facilities** Eye wash

## Advice to Doctor

**Advice to Doctor** Treat symptomatically.

## Other Health Hazard Information

## PRECAUTIONS FOR USE

**Exposure Limits** No exposure standard is available for this material as such however, once material has cured, the exposure standard for inspirable dust may apply:  
TWA: 10mg/m<sup>3</sup> (NOHSC-1995)  
TWA is the time weighted average concentration of the work atmosphere over a normal 8-hour work day and a 40-hour work week. Nearly all workers may be repeatedly exposed to this level, day after day, without adverse effect. These TWAs are issued as guidelines for good practice. All atmospheric contamination should be kept to as low a level as is practically possible. These TWAs should not be used as fine lines between safe and dangerous concentrations.

**Eng. Controls** Natural ventilation should be sufficient for normal use however, if using in confined or poorly ventilated areas, mechanical ventilation may be required.

## Personal Protection

**Protective Equip.** Avoid contact with skin and eyes and avoid breathing vapours. The following personal protective clothing is recommended:  
Respiratory protection if ventilation inadequate.  
Safety glasses recommended if there is risk of material entering the eyes.  
Protective gloves recommended if repeated or prolonged skin contact is expected.

## Flammability

**Fire Hazards** Non flammable.

## SAFE HANDLING INFORMATION

### Storage and Transport

**Storage and Transport** Store in cool, dry conditions away from oxidising agents and acids.

**Proper Shipping Name** None Allocated

### Spills and Disposal

**Spills & Disposal** Shovel into clearly labelled containers for either re-use or disposal as per statutory regulations.

### Fire/Explosion Hazard

**Fire/Explos. Hazard** This material is not flammable however, once the water has evaporated the dried film will burn.  
Hazardous decomposition products on burning: oxides of carbon and nitrogen, possible trace amounts of sulphur and chlorine compounds, smoke and fumes.  
Fire-fighting personnel to wear self-contained breathing apparatus and protective clothing.  
Extinguishing media: Foam, carbon dioxide.

**Hazardous Reaction** Incompatible with strong oxidising agents and acids.

**Hazchem Code** None Allocated

## OTHER INFORMATION

Continued on next page

# Material Safety Data Sheet

Page 3 of 3

Infosafe No. 2BKCZ	Issue Date: November 2002	ISSUED by BOSTIK
--------------------	---------------------------	------------------

Product Name: **PRO FILL A GAP 475GM**

Not classified as hazardous according to criteria of NOHSC

---

<b>Toxicology</b>	No toxicity data is available for this material.
<b>Technical Data</b>	Refer Product Information Bulletin
<b>Other Information</b>	N/A - None Allocated NOHSC - National Occupational Health & Safety Commission (Worksafe Aust.)

---

## CONTACT POINT

---

**Contact** & 24 hour Emergency Telephone  
Regulatory Affairs Officer  
ph (03) 9279 9320 or  
mobile 0419 335 187  
...End Of MSDS...